

RC840T Series

Compatible with 2- and 3-wire thermostats, this all-in-one relay includes a built-in 24 V transformer



 [Print this page](#)

MODELS & RATINGS

RC840T-240	4575 W @ 208 V	22 A resistive	FLA 13 / LRA 42
	5280 W @ 240 V	22 A resistive	FLA 12 / LRA 42
RC840T-277	5260 W @ 277 V	19 A resistive	
RC840T-347	6245 W @ 347 V	18 A resistive	

All above models operate on 50/60 Hz

SPECIFICATIONS

CONTROL SIGNAL

24 VAC / 40 mA

TRANSFORMER RATINGS

24 VAC / 1.2 VA / Class 2

HUMIDITY LIMITS

0 to 95 % non-condensing

TERMINAL WIRE SIZE

12 AWG

DIMENSIONS (H•W•D)

68 x 82 x 36 mm
2.7 x 3.2 x 1.4 inches

FEATURES

Direct replacement for any brand name relay

Built-in 24 V transformer for easy installation

Compatible with 24 V thermostats with 2-wire connections (R, W) or 3-wire connections (R, W, C)

Immediate relay activation provides improved temperature control and comfort

Epoxy-soundproofed relay ensures quiet operation

Low current consumption means multiple relays can be controlled by a single thermostat

Heating command indicator light gives at-a-glance verification of relay operation

Terminal board connection enables easy installation


ADDITIONAL INFORMATION

COMPATIBLE WITH AUBE THERMOSTATS:

TH113-A-024T
TH115-A-024T
TH116-A-024T
TH131-A-024T
TH132-A-024T
TH135-01
TH140-28-01
TH150 Series

INSTRUCTION MANUAL

 [RC840T.pdf](#) (format PDF)

 To view a PDF, you must have Acrobat Reader. Click on the icon to download it for free.

WARRANTY

